



SUPER FOAM 380

<h1>Technical Data</h1>	Foaming Industrial Renovator, Cleaner & Degreaser					
	DESCRIPTION:	Blue liquid, mild sweet odour.				
USED FOR:	Super Foam 380 is specially formulated to penetrate and emulsify soil, grease, oily substances and other deposits commonly found on machinery, equipment and other hard surfaces in industrial and food processing applications.					
ADVANTAGES:	<p>When used with a pressure washer or foamer, it produces a penetrating and cleaning foam blanket. Once the blanket is rinsed off, the accumulated deposits will have been emulsified, leaving a clean surface. Super Foam 380 is effective on industrial oils as well as food processing oils and fats.</p> <p>Super Foam 380 produces a super foaming action. Cuts labour time and costs. Penetrates and emulsifies soils, grease and oils. Excellent wetting and spreading characteristics. Highly concentrated. Non corrosive. Non flammable. Biodegradable.</p>					
DIRECTIONS:	<p>Refer to your pressure washer or foamer instruction manual to install the chemical feed suction lines and hoses. Dilution rates will vary with the type and make of the pressure washer or foamer equipment being used. Normal dilution ratios are from 1:5 to 1:40 Super Foam 380 to water.</p> <p>Apply the Super Foam 380 solution to thoroughly wet the surfaces to be cleaned. Start at the bottom and work up. Allow 5 to 10 minutes for maximum penetration of soils. Flush the surface thoroughly. Rinse vertical surfaces from top to bottom.</p> <p>*Do not use as a glass cleaner. Super Foam 380 is approved for use in registered food processing establishments.</p>					
	Package Size: (code)	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; text-align: center;">210 L 281516</td> <td style="width: 50%; text-align: center;">120 L 281514</td> </tr> <tr> <td style="text-align: center;">22.7 L 281511</td> <td></td> </tr> </table>	210 L 281516	120 L 281514	22.7 L 281511	
210 L 281516	120 L 281514					
22.7 L 281511						

Kem Canada Mfg., Brampton, Ontario, Canada L6T 2H5
800.263.2523 www.kemmfg.com